

CRNM-4K24-012W



The Colex LED Mini-Corn Series is used for indoor lighting; School; Hospital; and those places which need lighting with energy saving and high color rendering and keep the original enclosure. 360 degrees light.

General Specifications

| | | | |
|----------------------------|--------------------------------------|---------------------------------------|---|
| Cap-Base | GX24U | Dimmable | No |
| Bulb | Mini Corn | Wattage Equivalent | 24 W CFL BASE: GX24Q-1; GX24Q-2, GX24Q-3GX24Q-4 |
| Bulb Finish | Plastic / aluminum | Rated Wattage | 12 W (+/-5%) |
| Light color | Warm / Bright / Natural / Cool White | Warranty | 5 Years |
| Nominal Lifetime | 50000 hours | Bulb Temperature Above Ambient | +20C |
| Working Temperature | -20C ~+40C | | |

Light Specifications

| | | | |
|-------------------------------------|-------------|------------------------------------|-----------------|
| Beam Angle | 360 ° | Color Rendering Index (CRI) | >82 |
| Correlated Color Temperature | 3000-6500 K | Luminous Efficacy | 135 Lumens/Watt |
| Lumens | 1600 | | |

Electrical Specifications

| | | | |
|----------------|--------------|-----------------------|-------|
| Wattage | 12.0W +/- 5% | Line Frequency | 60 HZ |
| Voltage | 100-277 VAC | Power Factor | >.95 |

Notes:

1. Use in a dry location only
2. Fits existing sockets and fixtures
3. Need to bypass ballast

4. GX24U fits base GX24Q-1; GX24Q-2, GX24Q-3GX24Q-4

